

Specifications	Range	UT204+
AC current (A)	400A 600A	$\pm(2.5\%+5)$
AC current frequency (Hz)	50Hz~100Hz	
DC current (A)	400A 600A	$\pm(2.5\%+5)$
AC voltage (V)	600V	$\pm(0.8\%+5)$
AC voltage frequency(Hz)	10Hz~10kHz 10Hz~60kHz	$\pm(0.5\%+2)$
DC voltage (A)	600V	$\pm(0.5\%+2)$
Resistance (Ω)	40M Ω 60M Ω	$\pm(0.8\%+2)$
Capacitance (F)	4mF 40mF 60mF	$\pm(4\%+5)$
Temperature ($^{\circ}\text{C}$)	-40 $^{\circ}\text{C}$ ~1000 $^{\circ}\text{C}$	$\pm(1.5\%+5)$
Frequency (Hz)	10Hz~10MHz	$\pm(0.1\%+4)$

Features

Display count	6000
Auto range	√
Jaw opening	28mm
True RMS	√
NCV	√
Live wire test	√
Continuity test	√
Diode	√
MAX/MIN	√
Relative mode	√
Zero mode	√
Data hold	√
Low battery indication	√
Auto power off	√

General Characteristics

Power	1.5V battery (R03) x 2
Display	37mm x 25mm
Product color	Red and grey
Product net weight	235g
Product size	215mm x 63mm x 36mm
Standard accessories	Batteries, test leads, Themocouple

Specifications	Range	UT201	UT202	UT202A	UT203	UT204A
AC current (A)	400A	$\pm(1\%+9)$	$\pm(1\%+9)$		$\pm(2.5\%+5)$	
	600A			$\pm(1.5\%+5)$		$\pm(2.5\%+5)$
DC current (A)	400A				$\pm(2\%+3)$	
	600A					$\pm(2\%+5)$
AC voltage (V)	600V	$\pm(1.2\%+5)$	$\pm(1.2\%+5)$	$\pm(1.2\%+5)$	$\pm(1\%+5)$	$\pm(1\%+5)$
DC voltage (V)	600V	$\pm(0.8\%+1)$	$\pm(0.8\%+1)$	$\pm(0.8\%+1)$	$\pm(0.8\%+1)$	$\pm(0.8\%+1)$
Resistance (Ω)	20M Ω	$\pm(1\%+2)$	$\pm(1\%+2)$	$\pm(1\%+2)$		
	40M Ω				$\pm(1\%+2)$	$\pm(1\%+2)$
Capacitance (F)	100 μ F					$\pm(4\%+3)$
Frequency (Hz)	10Hz~10MHz				$\pm(0.1\%+3)$	$\pm(0.5\%+3)$
Temperature	-40°C~1000°C		$\pm(1\%+7)$			$\pm(2.5\%+3)$
	-40°F~1832°F		$\pm(1\%+8)$			
Display count		2000	2000	2000	4000	4000
Auto range		√	√	√	√	√
General Characteristics						
Power	UT201/UT202: 1.5V battery (R03) x 2; UT202A/UT203/UT204A: 9V battery (6F22)					
Display	35.6mm x 18mm					
Product color	Red and grey					
Product net weight	UT201/UT202/UT202A: 220g; UT203/UT204A: 260g					
Product size	UT201/UT202/UT202A: 210mm x 75.6mm x 30mm; UT203/UT204A: 208mm x 76mm x 30mm					
Standard accessories	Batteries, test leads, carrying bag, point contact temperature probe (UT202/UT204A)					